


## CHEST HEATED IRONERS - ONE ROLL

ACL500

ACL  
RANGE



### FEATURES

#### Chest

- Single piece super flexible laser welding chest have 180-206° wrap up contact to rolls
- Self-adjusted chest applies pressure always equally over entire width and length of the roll.  
To make linen being ironed equal quality.
- Heated by circulated thermal oil moving in the chest. It makes the temperature even along full chest width. No trouble of overheated spots.
- Self-contained thermal oil heating and circulation system offers accurate temperature control, easy installation and start up
- Steam heated by steam injection directly into the chest

#### Delivery

- Front return to save operation space and one person to operate
- Rear return to connect folder when necessary
- Front and rear return optional to be flexible to suit the laundry flow

#### Roll

- Perforated steel roll with under springing and polyester felt 800 gr/m<sup>2</sup> padding
- Suction through the roll to ventilate moisture
- Fully enclosed planetary gearbox mounted directly onto the roll
- Variable speed by frequency inverter drive

#### Control

- Simple readout control to set temperature and speed manually
- Optional PLC touch screen with 50 programs. Speed regulation and modulating burner included.

### OPTIONS

- Unique high ventilation chest for 25% higher output (not for steam heating)
- Higher ironing speed
- Longer feeding table
- Foot pedal
- M-Aramid padding

TYPE		ACL500-17	ACL500-20	ACL500-22	ACL500-25	ACL500-30	ACL500-33
Roll diameter	mm			500			
Working width	mm	1750	2000	2200	2500	3000	3300
Ironing speed	m/min			1,5-5,5			
High ironing speed	m/min			1,5-12			
Fan motor	kW			0,25			
Roll motor	kW			0,37			
Roll motor, high speed	kW			1,5			
Exhaust diameter	mm			Ø75			
Hydraulic pump motor	kW			0,37			
Oil circulation pump	kW			2,2			
Voltage		380-415V/50Hz/3ph+TN-C					
<b>GAS HEATING</b>							
Gas connection	inch			1/2"			
Gas pressure	mbar			20			
Gas consumption	kW	34	39	43	50	60	65
Heat exchanger evacuation	mm			Ø90			
Ironing capacity @moisture retention 50%	kg/hr	65	75	82	95	115	125
<b>STEAM HEATING</b>							
Steam pressure	bar			6-12			
Steam connection	inch			5/4"			
Condens connection	inch			3/4"			
Steam consumption @ 10bar	kg	50	57	63	72	88	95
Ironing capacity @moisture retention 50%	kg/hr	58	67	74	85	103	112
<b>ELECTRIC HEATING</b>							
Heating element	kW	30	30	35	40	45	45
Ironing capacity @moisture retention 50%	kg/hr	65	75	82	95	115	125
<b>DIMENSIONS</b>							
Width	mm	2600	2850	3050	3350	3850	4150
Depth	mm	1715	1715	1715	1715	1715	1715
Height	mm	1200	1200	1200	1200	1200	1200
Net weight	kg	1000	1200	1270	1350	1475	1600
<b>TRANSPORT DATA</b>							
Width	mm	2700	2950	3150	3450	3950	4250
Depth	mm	1195	1195	1195	1195	1195	1195
Height	mm	1300	1300	1300	1300	1300	1300
Gross weight	kg	1030	1230	1300	1380	1505	1630